

KloudStor kStore 2U24 EBOD is the datasphere's ideal platform for Storage expansion, supporting efficient growth, performance, and high capacity at an affordable price.

Key Advantages



Product Highlights

- **Transfer Data Fast With a 12 Gb/s SAS Interface** - Get data to applications when and where it's needed with up to 12 Gb/s speed, right-sized capacity, and effective maximum throughput of 14.4 GB/s in a single I/O module or 28.8 GB/s in a dual controller configuration. Even with expansion capability of up to 144 hard drives or solid-state drives, there is no sacrifice of space for performance.
 - **Deliver Versatile Architecture Built to Grow** - This flexible enclosure includes support and capabilities to manage cables, universal ports, self-configuration controls and standardized zoning. As a key building block of our modular systems — which make all critical components interchangeable regardless of size or budget — this enclosure's modularity makes it easy to set up, maintain, and expand via interchangeable FRUs and hot-swappable components.
 - **Ensure Applications Have Access to Critical Data** - Safeguard your data with fault diagnosis, resolution capabilities, persistent error logging, and monitoring while ensuring maximum availability and harnessing high-availability features such as dual PCMs and I/O modules, as well as dual data paths to all drives.
 - **Reduce Cost and Resources With Energy-Efficient Features** - This enclosure is suited for high-capacity, transaction-dependent environments that demand tighter Service Level Agreement (SLA) requirements and need faster response times for optimal data availability. It meets stringent worldwide requirements for recycling and environmental friendliness, can help you minimise environmental impact, and recognise cost savings through high performance and efficiency.
 - **Reduce power consumption** - 80 PLUS Gold and 80 PLUS Platinum power supply options with certified adaptive cooling technology.
 - **Build In Security at the Foundation of the Data Life Cycle** - Protect your most valuable business assets with guaranteed compatible Seagate Secure™ hard drives.
- Save space with up to 24 SFF drives in a 2U rackmount enclosure
 - Expansion for your high-performance deployments
 - Safeguard data with intelligent fault diagnosis, resolution capabilities, persistent error logging, and monitoring
 - Use the latest Drive Technologies.
 - Ensure data is available with N+1 PCMs, I/O modules, and dual data paths to all drives
 - Maximum of 28.8 GB/s in a dual controller configuration

ABOUT KLOUDSTOR

With extensive experience in enterprise data protection and storage management, KloudStor focuses on serving and meeting the growing data needs of customers with innovative and highly scalable 'On-Premise as-a-Service' solutions. With a flexible pay-per-consumption monthly subscription model, we provide the best of on-premise performance and security with cloud flexibility.

KloudStor's fully managed solutions are supported by a team of highly skilled and experienced data management experts. Our partnerships with Quantum and Seagate, leading technology companies in the field of data storage and backup, enable us to provide proven, robust and trusted as-a-Service solutions for our customers ensuring that their operations and businesses are running continuously without compromise.

KloudStor

www.kloudstor.asia
enquiry@kloudstor.asia

133 New Bridge Road #08-03
Chinatown Point
Singapore 059413

TECHNICAL SPECIFICATIONS

SPECIFICATIONS	
Redundant Path	Dual I/O modules per enclosure
Host/Expansion I/O Ports	Three universal ×4 12 Gb/s mini-SAS HD connectors (SFF-8644) per I/O module
Management/Status Reporting	CLI via RS232 and 100Base-T port SES via SAS SFF-8644 ports
Maximum System Configuration	10 Total Enclosures including Master
Device Support	Dual-port 12 Gb/s and 6 Gb/s SAS drives
Max Drives Per Enclosure	24 (for a full list of supported drives, please contact your account or sales manager)
Hot-Swappable Components	Drives, power cooling modules (PCM), and SBB I/O modules
Physical	Height: 88.9 mm/3.5 in (2 EIA units) Width: 483 mm/19 in (IEC rack compliant) Depth: 630 mm/24.8 in Weight: 24 kg/53 lb (with drives)
Power Requirements - AC Input	
Input Power Requirements	90VAC-264VAC, 50 Hz/60 Hz
Max Power Output per PSU	580W
Environmental/Temperature Ranges	
Operating/Non-operating Altitude	0 m to 3,000 m (0 ft to 10,000 ft)/-300 m to 12,192 m (-1,000 ft to 40,000 ft)
Operating/Non-operating Temperature	ASHRAE A3, 5°C to 40°C (41°F to 104°F), derate 1°C/175m above 900m, 20°C/hr max rate of change / -40°C to 70°C (-40°F to 158°F)
Operating/Non-operating Humidity	-12°C DP and 10% RH to 21°C DP and 80% RH, max DP 21°C / 5% to 100% non-condensing
Operating/Non-operating Shock	5 Gs, 10ms, half sine pulses/15 Gs, 10ms, half sine pulses
Operating/Non-operating Vibration	0.21 Gs rms (5-500Hz) / 1.04 Gs rms (2-200Hz)
Power Supply Units	
Power Supply	Ecodesign (Part SP-PCM01-HE580-AC/Model FS580FS104G-XX) - Gold Power Efficiency 115VAC/60 Hz 230VAC/50 Hz Power Factor Condition 10% Load = >80% >80% 10% Loading = N/A 20% Load = >87% >88% 20% Loading = >0.90 50% Load = >90% >92% 50% Loading = >0.90 100% Load = >87% >88% 100% Loading = >0.95
Power Supply	Ecodesign (Part SP-PCM4-PT580-AC/Model SGT-S-0580ADU00) - Platinum Power Efficiency 115VAC/60 Hz 230VAC/50 Hz Power Factor Condition(PFC) 10% Load = >80% >80% 10% Loading = N/A 20% Load = >90% >90% 20% Loading = >0.90 50% Load = >92% >94% 50% Loading = >0.95 100% Load = >89% >91% 100% Loading = >0.95