

KloudStor kStore 5U84 EBOD is the datasphere's ideal platform for Storage expansion, supporting efficient growth, performance, and high capacity at an affordable price.

Key Advantages



Product Highlights

- Deliver peace of mind with features to protect data, including dual power supplies, fan modules, and I/O modules, as well as dual data paths to all drives
- Easily manage cables, universal ports, self-configuration controls, and standardised zoning
- Seamlessly expand to 336 drives as business grows
- Efficiently manage your data centre with a 5U rackmount enclosure and unique drawer design that provides easy access to drives
- Maximum of 28.8 GB/s in a dual controller configuration
- **Transfer Data Fast With a 12 Gb/s SAS Interface** - Get data to applications when and where it's needed with up to 12 Gb/s speed, remarkable capacity, and effective maximum throughput of 14.4 GB/s in a single I/O module or 28.8 GB/s in a dual controller configuration. Even with an expansion capability of up to 336 hard drives or solid-state drives, there is no sacrifice of space for performance.
- **Deliver a Versatile Architecture Built to Grow** - Minimise your TCO and store PBs of data within a single enclosure that leads the industry in both density and cost-for-performance while enabling easy multi-enclosure expansion via interchangeable FRUs and SBB 2.0 compatibility. This flexible enclosure includes support and capabilities to manage cables, universal ports, self-configuration controls, and standardized zoning while helping you accelerate the market introduction of new technologies and significantly simplify the development and testing of storage implementations.
- **Ensure Applications Have Access to Critical Data** - Safeguard your data with fault diagnosis, resolution capabilities, persistent error logging, and monitoring while ensuring maximum availability and harnessing high-availability features such as dual cooling, PCMs, and I/O modules, as well as dual data paths to all drives.
- **Reduce Cost and Resources With Energy-Efficient Features** - This enclosure is suited for high-capacity, transaction-dependent environments that demand tighter Service Level Agreement (SLA) requirements and need faster response times for optimal data availability. It meets stringent worldwide requirements for recycling and environmental friendliness, can help you minimise environmental impact, and recognise cost savings through high performance.
- **Reduce power consumption** - 80 PLUS Titanium and 80 PLUS Platinum power supply options with certified adaptive cooling technology.

ABOUT KLOUDSTOR

With extensive experience in enterprise data protection and storage management, KloudStor focuses on serving and meeting the growing data needs of customers with innovative and highly scalable 'On-Premise as-a-Service' solutions. With a flexible pay-per-consumption monthly subscription model, we provide the best of on-premise performance and security with cloud flexibility.

KloudStor's fully managed solutions are supported by a team of highly skilled and experienced data management experts. Our partnerships with Quantum and Seagate, leading technology companies in the field of data storage and backup, enable us to provide proven, robust and trusted as-a-Service solutions for our customers ensuring that their operations and businesses are running continuously without compromise.

KloudStor

www.kloudstor.asia
enquiry@kloudstor.asia

133 New Bridge Road #08-03
Chinatown Point
Singapore 059413

TECHNICAL SPECIFICATIONS

SPECIFICATIONS	
Controller	Dual EBOD storage bridge bay (SBB) 2.1 compatible I/O modules per enclosure
Host/Expansion Interface	Three universal ×4 12 Gb/s mini-SAS connectors (SFF-8644) per I/O module
Management/Status Reporting	CLI via RS232 and 100Base-T port SES via SAS SFF-8644 ports
Maximum System Configuration	Dual host-connected enclosure with a maximum expanded configuration of 4 enclosures for a total of 336 drives
Device Support	Dual-ported 12 Gb/s SAS
Max Drives Per Enclosure	84 (for a full list of supported drives, please contact your account or sales manager)
Hot-Swappable Components	Drives, power supply units (PSU), cooling modules, side planes, and SBB I/O modules
Physical	Height: 220 mm/8.65 in (5 EIA units) Width: 483 mm/19 in (IEC rack compliant) Depth: 933 mm/36.75 in Weight: 135 kg/298 lb (with drives, no rail kit)
Power Requirements - AC Input	
Input Power Requirements	180VAC-240VAC, 50Hz/60Hz
Max Power Output per PSU	2200W
Environmental/Temperature Ranges	
Operating/Non-operating Altitude	- 100 m to 3,000 m (-330 ft to 10,000 ft) / - 100 m to 12,192 m (-330 ft to 40,000 ft)
Operating/Non-operating Temperature	ASHRAE A2, 5°C to 35°C (41°F to 95°F), derate 1°C / 300m above 900m, 20°C / hr max rate of change / -40°C to 70°C (-40°F to 158°F)
Operating/Non-operating Humidity	- 12°C DP and 10% RH to 21°C DP and 80% RH, max DP 21°C / 5% to 100% non-condensing
Operating/Non-operating Shock	5 Gs, 10 ms, half sine pulses/20 Gs, 10 ms, half sine pulses
Operating/Non-operating Vibration	0.21 Gs rms (5-500Hz) / 1.04 Gs rms (2-200Hz)
Power Supply Units	
Power Supply	<div><div>Ecodesign (Part UD-PCM2-2200-AC/ Model SGT-S-2200ADE00) - Titanium</div><div><div>Power Efficiency 230VAC50/Hz</div><div>10% Load = >90%</div><div>20% Load = >94%</div><div>50% Load = >96%</div><div>100% Load = >91%</div></div><div><div>Power Factor Conditions (PFC)</div><div>10% Loading = >0.8</div><div>20% Loading = >0.9</div><div>50% Loading = >0.95</div><div>100% Loading = >0.95</div></div></div>
Power Supply	<div><div>Ecodesign (Part UD-PSU01-2200-AC/ Model FS2K2HS180-xx) - Platinum</div><div><div>Power Efficiency 230VAC50/Hz</div><div>10% Load = >81%</div><div>20% Load = >89%</div><div>50% Load = >93%</div><div>100% Load = >90%</div></div><div><div>Power Factor Conditions (PFC)</div><div>10% Loading = >0.80</div><div>20% Loading = >0.90</div><div>50% Loading = >0.95</div><div>100% Loading = >0.95</div></div></div>